

AIRCRAFT CABIN LEAKAGE TESTER

400 SCFM, Electric Driven

P/N: 96384-100, NSN: 4920-01-435-8545



HYDRAULICS INTERNATIONAL, INC.

9201 Independence Avenue, Chatsworth, CA 91311, U.S.A.

Tel: +1(818) 718-2462

Fax: +1(818) 718-2459

Website: www.hiigroup.com

The technical information contained on this product sheet is current as of this publishing. Information contained herein is subject to revision without advanced notification from the manufacturer. For the most recent up-to-date information, please contact Hydraulics International, Inc. All rights reserved ©2011 Hydraulics International, Inc.

Aircraft Cabin Leakage Tester, Electric Driven

P/N 96384-100, NSN: 4920-01-435-8545

General information (400 SCFM):

The cabin leakage tester is a self-contained towable unit. The unit provides a means of pressurizing and automatically measuring the leakage rate of an aircraft cabin.

The tester consists principally of: a positive displacement lobe blower which supplies compressed atmospheric air at a desired operating pressure and a controlled temperature. In

addition, a separately driven compressor provides the means to pressurize the aircraft canopy seal.

In addition to the blower and prime mover electric motor the unit consists of: an after-cooler assembly, a flowmeter, and control panel with appropriate instrumentation.

Auxiliary equipment includes: supply and pressure monitor hoses, adapters and a stethoscope.

Leading Particulars

Operating Characteristics:	
Medium	Compressed air
Pressure, Cabin	2 through 12.5 psig range
Flow	0 through 400 scfm
Temperature	25° above ambient temperature at maximum flow and pressure
Pressure, Canopy Seal	65 psig max.
Flow, Canopy Seal	1.4 scfm
Operating Ambient Temperature	
Range	-20° to +120°F
Altitude Operating	
Range	Sea Level to 6,000 ft.
Storage Temperature	
Range	-60°F to +160°F
Operating Positions 8½ degree incline with true horizontal plane	
Tow Speed 20 mph improved roads, 10 mph unimproved roads	
Cramping Angle 40 degrees	
Tire Inflation 60 psig	
Power Equipment:	
Electric Motor	60 HP, 460/230/208 VAC, 3 Phase, 50/60 HZ
Blower	Single stage, positive-displacement, lobe type
After-cooler	Air-to-air, sized to maintain blower discharge air within 25°F above ambient at maximum flow and pressure
Relief Valve	Adjustable, pilot controlled, 2 to 14 psig range
Rate Valve	Adjustable, pilot controlled, limits pressure increase or decrease rate
Compressor	Oil-less reciprocating air compressor, electric motor driven, 1.4 scfm, 65 psig max.
Instrumentation:	
Pressure Gage:	(1) Cabin pressure, 0-15 psig range (1) Blower pressure, 0-20 psig range (1) Canopy seal pressure, 0-100 psig range
Pressure Rate of Change	(1) Rate of cabin pressure change, 0 to 6000 ft per minute rate increasing and decreasing
Temperature	(1) Discharge air temperature -20°F to +140°F range
Flowmeter (2 stage).....	(1) Rotometer Type, 0 to 400 scfm, 2 to 14 psig range
Overall Dimensions	
	Height: 68 inches Length: 107 inches Width: 57 inches
Weight (Dry)	
	App. 3070 pounds



HYDRAULICS INTERNATIONAL, INC.

9000 Mason Avenue, Chatsworth, CA 91311

www.hiigroup.com

Tel.: (818) 718-2462

Fax: (818) 718-2459

Email: sales@hiinet.com